

mmm62264912304

①

3M MATERIAL SAFETY DATA SHEET 3M(TM) Concrete Repair DP-600, Self-Leveling, Gray 12/19/2003



Material Safety Data Sheet

Copyright, 2003, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M(TM) Concrete Repair DP-600, Self-Leveling, Gray

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes

ADDRESS: 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/19/2003

Supersedes Date: 07/22/2003

Document Group: 18-0740-3

ID Number(s):

62-2649-1230-4, 62-2649-1233-8, 62-2649-1235-3, 62-2649-5030-4, 62-2649-5037-9

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

18-0901-1, 18-0894-8

Revision Changes:

Page Heading: Product name was modified.

Kit: Product name was modified.

Kit: ID number(s) was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

②



Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M(TM) Concrete Repair 600, Self-Leveling, Gray (Part A)

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 01/11/2005

Supersedes Date: 01/29/2004

Document Group: 18-0894-8

Product Use:

Specific Use: Two-part urethane adhesive/sealant.

Formerly known as DYNAMix(TM) Self-Leveling Rapid Repair 6143-1, Gray.

Ingredient

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
4,4'-diphenylmethane diisocyanate	101-68-8	30 - 60
diphenylmethanediisocyanate prepolymer	68424-09-9	15 - 40
poly(diphenylmethane-4,4'-diisocyanate)	25686-28-6	15 - 40
amorphous silica	7631-86-9	1 - 5

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Viscous

Odor, Color, Grade: Low or no detectable odor, opaque.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: respiratory reaction.

May cause allergic skin reaction.

May cause allergic

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Prolonged or repeated exposure may cause:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Prolonged or repeated exposure may cause:

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

Target Organ Effects:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

(4)

If Swallowed: Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

Not Applicable

Flash Point

$\geq 290^{\circ}\text{F}$ [Test Method: Tagliabue Closed Cup]

Flammable Limits - LEL

Not Applicable

Flammable Limits - UEL

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may be used to blanket the fire. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Non-flammable: ordinary combustible material.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

Accidental Release Measures: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid eye contact with vapors, mists, or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe vapors.

7.2 STORAGE

Store away from acids.

5

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust for cutting, grinding, sanding or machining. Do not use in a confined area or areas with little or no air movement.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**8.2.1 Eye/Face Protection**

Avoid eye contact with vapors, mists, or spray.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber, Nitrile Rubber.

8.2.3 Respiratory Protection

Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe vapors.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
amorphous silica	CMRG	CEIL	5 mg/m3	
FREE ISOCYANATES	3M	TWA	0.005 ppm	
FREE ISOCYANATES	3M	STEL	0.02 ppm	
4,4'-diphenylmethane diisocyanate	ACGIH	TWA	0.005 ppm	
4,4'-diphenylmethane diisocyanate	OSHA	CEIL	0.02 ppm	Table Z-1

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

Specific Physical Form:**Odor, Color, Grade:****General Physical Form:****Autoignition temperature****Flash Point****Flammable Limits - LEL****Flammable Limits - UEL**

Viscous

Low or no detectable odor, opaque.

Liquid

Not Applicable

≥ 290 °F [Test Method: Tagliabue Closed Cup]

Not Applicable

Not Applicable

6

Boiling point	>=400 °F
Vapor Density	>=1 [Ref Std: AIR=1]
Vapor Pressure	<=0.000004 mmHg [@ 68 °F]
Specific Gravity	1.11
pH	Not Applicable
Melting point	No Data Available
Solubility in Water	Negligible
Evaporation rate	<=1 [Details: Gels with exposure to humidity.]
Volatile Organic Compounds	<=10 g/l [Test Method: calculated per EPA method 24]
Volatile Organic Compounds	<=5 g/l [Test Method: calculated per EPA method 24] [Details: Mixed 1:1 with Part B]
Percent volatile	<=1 % volume [Test Method: Estimated]
Percent volatile	<=0.5 % volume [Test Method: Estimated] [Details: Mixed 1:1 with Part B]
VOC Less H2O & Exempt Solvents	<=10 g/l [Test Method: calculated per EPA method 24]
VOC Less H2O & Exempt Solvents	<=5 g/l [Test Method: calculated per EPA method 24] [Details: Mixed 1:1 with Part B]
Viscosity	1,250 - 2,750 centipoise

Stability: Stable.

Materials and Conditions to Avoid: Water; Strong acids; Strong bases

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

ECOTOXICOLOGICAL INFORMATION

Not determined.

7

CHEMICAL FATE INFORMATION

Not determined.

Waste Disposal Method: Dispose of completely cured (or polymerized) wastes in a sanitary landfill. As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

ID Number(s):

62-2749-8535-7, 62-2749-9535-6

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
4,4'-diphenylmethane diisocyanate (Diisocyanates (EPCRA 313))	101-68-8	30 - 60

8

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 16: HMIS hazard classification heading was modified.

Section 3: Other potential health effects heading was modified.

Copyright was modified.

Section 8: Exposure guidelines data source legend was modified.

Section 3: Potential effects from eye contact was modified.

Section 3: Potential effects from skin contact information was modified.

Section 3: Potential effects from inhalation information was modified.

Section 7: Handling information was modified.

Section 7: Storage information was modified.

Section 8: Engineering controls information was modified.

Section 8: Eye/face protection phrase was modified.
Section 8: Skin protection phrase was modified.
Section 15: 311/312 hazard categories heading was modified.
Section 15: International regulations information was modified.
Section 15: State regulations information was modified.
Section 15: US federal regulations information was modified.
Section 10: Hazardous polymerization heading was modified.
Section 14: Transportation legal text was modified.
Section 3: Other health effects information was modified.
Section 16: HMIS explanation was modified.
Section 15: Inventories information was modified.
Section 15: EPCRA 313 text was modified.
Section 12: Ecotoxicological information heading was modified.
Section 12: Chemical fate information heading was modified.
Section 12: Ecotoxicological phrase was modified.
Section 12: Chemical Fate phrase was modified.
Section 16: NFPA hazard classification heading was added.
Section 16: NFPA hazard classification for health was added.
Section 16: NFPA hazard classification for flammability was added.
Section 16: NFPA hazard classification for reactivity was added.
Section 16: NFPA explanation was added.
Section 16: NFPA hazard classification for special hazards was added.
Section 2: Ingredient phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M(TM) Concrete Repair 600, Self-Leveling, Gray (Part B)
MANUFACTURER: 3M
DIVISION: Industrial Adhesives and Tapes

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 01/11/2005
Supersedes Date: 01/29/2004

Document Group: 18-0901-1

Product Use:

Specific Use: Two-part urethane adhesive/sealant.

Formerly known as DYNAMix(TM) Self-Leveling Rapid Repair 6143-1, Gray.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
Polyether Polyol	9082-00-2	40 - 70
Propoxylated Trimethylolpropane	25723-16-4	10 - 30
Tetrakis(2-hydroxypropyl)ethylenediamine	102-60-3	10 - 30
Amorphous Silica	68611-44-9	1 - 5
m-Xylene-alpha,alpha-diamine	1477-55-0	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l Sebacate	41556-26-7	0.1 - 1
Polymeric Benzotriazole Derivative	104810-48-2	0.1 - 0.3
Polymeric Benzotriazole	104810-47-1	0.1 - 0.3
Substituted Piperidiny Sebacate	82919-37-7	0.05 - 0.2

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Viscous

Odor, Color, Grade: Slight ammonia like odor, gray.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards:

May cause allergic skin reaction.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Prolonged or repeated exposure may cause:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

If Swallowed: Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

(12)

5.1 FLAMMABLE PROPERTIES

Autoignition temperature
Flash Point
Flammable Limits - LEL
Flammable Limits - UEL

Not Applicable
≥290 °F [Test Method: Tagliabue Closed Cup]
Not Applicable
Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable. Non-flammable: ordinary combustible material.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Ventilate the area with fresh air. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect as much of the spilled material as possible. Clean up residue with an appropriate organic solvent. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid eye contact with vapors, mists, or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from oxidizing agents.

8.1 ENGINEERING CONTROLS

(13)

Provide appropriate local exhaust for cutting, grinding, sanding or machining.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber.

8.2.3 Respiratory Protection

Avoid breathing of dust created by cutting, sanding, grinding or machining.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) Sebacate	CMRG	TWA	1 mg/m3	
m-Xylene-alpha,alpha-diamine	ACGIH	CEIL	0.1 mg/m3	Skin Notation*
m-Xylene-alpha,alpha-diamine	OSHA	CEIL	0.1 mg/m3	Table Z-1A

* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

Specific Physical Form:
Odor, Color, Grade:
General Physical Form:
Autoignition temperature
Flash Point
Flammable Limits - LEL
Flammable Limits - UEL
Boiling point

Viscous
 Slight ammonia like odor, gray.
 Liquid
 Not Applicable
 >=290 °F [Test Method: Tagliabue Closed Cup]
 Not Applicable
 Not Applicable
 >=400 °F

Vapor Density

>=1 [Ref Std: AIR=1]

(14)

3M MATERIAL SAFETY DATA SHEET 3M(TM) Concrete Repair 600, Self-Leveling, Gray (Part B) 01/11/2005

Vapor Pressure	Not Applicable
Specific Gravity	1.04
pH	Not Applicable
Melting point	No Data Available
Solubility in Water	Negligible
Evaporation rate	<=1 [Ref Std: WATER=1]
Hazardous Air Pollutants	00 % weight [Test Method: Calculated]
Volatile Organic Compounds	<=10 g/l [Test Method: calculated per EPA method 24]
Volatile Organic Compounds	<=5 g/l [Test Method: calculated per EPA method 24] [Details: Mixed 1:1 with Part A]
Percent volatile	<=1 % volume [Test Method: Estimated]
Percent volatile	<=0.5 % volume [Test Method: Estimated] [Details: When mixed 1:1 with Part A]
VOC Less H2O & Exempt Solvents	<=10 g/l [Test Method: calculated per EPA method 24]
VOC Less H2O & Exempt Solvents	<=5 g/l [Test Method: calculated per EPA method 24] [Details: Mixed 1:1 with part A]
Viscosity	3,200 - 5,600 centipoise

Stability: Stable.

Materials and Conditions to Avoid: Strong acids; Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Oxides of Nitrogen	During Combustion

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

ECOTOXICOLOGICAL INFORMATION

Not determined.

(15)

CHEMICAL FATE INFORMATION

Not determined.

Waste Disposal Method: Dispose of completely cured (or polymerized) wastes in a sanitary landfill. As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material. Combustion products will include HCl. Facility must be capable of handling halogenated materials.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

ID Number(s):
62-2649-8535-9, 62-2649-9535-8

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

(16)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 16: HMIS hazard classification heading was modified.
Copyright was modified.
Section 8: Exposure guidelines data source legend was modified.
Section 3: Potential effects from eye contact was modified.
Section 3: Potential effects from inhalation information was modified.
Section 5: Unusual fire and explosion hazard information was modified.
Section 7: Handling information was modified.
Section 8: Eye/face protection phrase was modified.
Section 8: Skin protection phrase was modified.
Section 8: Respiratory protection information was modified.
Section 15: 311/312 hazard categories heading was modified.
Section 15: International regulations information was modified.
Section 15: State regulations information was modified.
Section 15: US federal regulations information was modified.
Section 4: First aid for inhalation - termination of exposure - was modified.
Section 4: First aid for inhalation - medical assistance - was modified.
Section 10: Hazardous polymerization heading was modified.
Section 14: Transportation legal text was modified.

(17)

Section 2: Ingredient table was modified.
Section 16: HMIS explanation was modified.
Section 15: 311/312 Delayed Hazard score was modified.
Section 15: Inventories information was modified.
Section 12: Ecotoxicological information heading was modified.
Section 12: Chemical fate information heading was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 12: Ecotoxicological phrase was modified.
Section 12: Chemical Fate phrase was modified.
Section 16: NFPA hazard classification heading was added.
Section 16: NFPA hazard classification for health was added.
Section 16: NFPA hazard classification for flammability was added.
Section 16: NFPA hazard classification for reactivity was added.
Section 16: NFPA explanation was added.
Section 8: Exposure guideline note was added.
Section 16: NFPA hazard classification for special hazards was added.
Section 2: Ingredient phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.