



## Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M™ EXTRACTION CLEANER (CONCENTRATE) (Product No. 9, Twist 'n Fill™ System)  
**MANUFACTURER:** 3M  
**DIVISION:** Commercial Care Division  
**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

**EMERGENCY PHONE:** 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 06/14/2005  
**Supersedes Date:** 06/06/2003  
**Document Group:** 06-2710-9

#### Product Use:

**Specific Use:** Low-foaming cleaner used to clean colorfast carpet with portable extraction machines.

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	40 - 70
HYDROXYALKYL AMINE OXIDES	68478-65-9	10 - 30
ISOPROPYL ALCOHOL	67-63-0	5 - 10
ETHYLENE GLYCOL ETHYLHEXYL ETHER	1559-35-9	1 - 5
DIETHYLENE GLYCOL MONO (2-ETHYLHEXYL) ETHER	1559-36-0	0.1 - 1

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Liquid

**Odor, Color, Grade:** Clear, colorless; mild fragrance

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Combustible liquid and vapor. May cause severe eye irritation. May cause allergic skin reaction. May cause target organ effects.

#### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Skin Contact:**

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

**Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

### 3.3 POTENTIAL ENVIRONMENTAL EFFECTS

A 3M Product Environmental Data Sheet (PED) is available.

A conservative assessment indicates this product presents a low environmental risk. Components released to the environment through use and disposal are expected to have insignificant environmental impacts.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature**

**Flash Point**

**Flammable Limits - LEL**

**Flammable Limits - UEL**

**OSHA Flammability Classification:**

Approximately 750 °F [*Details:* Isopropyl alcohol]

102 °F [*Test Method:* Closed Cup]

2.0 % volume [*Details:* Isopropyl alcohol]

12.7 % volume [*Details:* @200F Isopropyl alcohol]

Class II Combustible Liquid

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Combustible liquid and vapor.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Keep out of the reach of children. This product is not intended to be used without prior dilution as specified on the product label. Avoid breathing of vapors, mists or spray. Avoid skin contact. Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid contact with oxidizing agents.

### 7.2 STORAGE

Store away from heat. Store out of direct sunlight. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use in a well-ventilated area.

NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, special ventilation is not required.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact.

NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, eye contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, the following eye protection is recommended: Indirect Vented Goggles, Full Face Shield.

#### 8.2.2 Skin Protection

Avoid skin contact.

NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, skin contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material is recommended: Butyl Rubber

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, respiratory protection is not required.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ISOPROPYL ALCOHOL	ACGIH	TWA	200 ppm	Table A4
ISOPROPYL ALCOHOL	ACGIH	STEL	400 ppm	Table A4
ISOPROPYL ALCOHOL	OSHA	TWA	400 ppm	Table Z-1A
ISOPROPYL ALCOHOL	OSHA	STEL	500 ppm	Table Z-1A

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists  
CMRG: Chemical Manufacturer Recommended Guideline  
OSHA: Occupational Safety and Health Administration  
AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid
Odor, Color, Grade:	Clear, colorless; mild fragrance
General Physical Form:	Liquid
Autoignition temperature	Approximately 750 °F [Details: Isopropyl alcohol]
Flash Point	102 °F [Test Method: Closed Cup]
Flammable Limits - LEL	2.0 % volume [Details: Isopropyl alcohol]
Flammable Limits - UEL	12.7 % volume [Details: @200F Isopropyl alcohol]
Boiling point	Approximately 200 °F
Density	Approximately 1 [Ref Std: WATER=1]
Vapor Density	Approximately 2 [Ref Std: AIR=1] [Details: Isopropyl alcohol]
Vapor Pressure	<=27 psia [@ 131 °F]
Specific Gravity	Approximately 1 [Ref Std: WATER=1]
pH	6 - 8
Solubility in Water	Complete
Evaporation rate	Approximately 1 [Ref Std: WATER=1]
Hazardous Air Pollutants	Not Applicable
Volatile Organic Compounds	15 - 40 % [Test Method: calculated per CARB title 2]
Percent volatile	No Data Available
Percent volatile	Not Applicable
VOC Less H2O & Exempt Solvents	327 - 871 g/l [Test Method: calculated per CARB title 2]
Viscosity	< 100 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

### CHEMICAL FATE INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number**  
70-0708-4009-8

**UPC**  
00-48011-20779-2

**ID Number**  
70-0710-0969-3

**UPC**  
00-48011-23892-5

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

#### 311/312 Hazard Categories:

Fire Hazard - Yes   Pressure Hazard - No   Reactivity Hazard - No   Immediate Hazard - Yes   Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ETHYLENE GLYCOL ETHYLHEXYL ETHER (GLYCOL ETHERS)	1559-35-9	1 - 5
DIETHYLENE GLYCOL MONO (2- ETHYLHEXYL) ETHER (GLYCOL ETHERS)	1559-36-0	0.1 - 1

## STATE REGULATIONS

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All the components of this product are listed on China's Inventory of Chemical Substances.

The components of this product are in compliance with notification requirements in the Philippines.

## INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

Health: 2 Flammability: 2 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

Health: 2 Flammability: 2 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

### Revision Changes:

Section 1: Product use information was modified.  
Section 16: NFPA hazard classification heading was modified.  
Section 16: HMIS hazard classification heading was modified.  
Section 3: Potential environmental effects heading was modified.  
Section 3: Other potential health effects heading was modified.  
Copyright was modified.  
Section 8: Exposure guidelines data source legend was modified.  
Section 3: Potential effects from skin contact information was modified.  
Section 3: Potential effects from inhalation information was modified.  
Section 3: Potential effects from ingestion information was modified.  
Section 5: Fire fighting procedures information was modified.  
Section 6: Release measures information was modified.  
Section 7: Handling information was modified.  
Section 8: Engineering controls information was modified.  
Section 8: Eye/face protection phrase was modified.  
Section 8: Skin protection phrase was modified.  
Section 8: Respiratory protection information was modified.  
Section 13: Waste disposal method information was modified.

Section 15: 311/312 hazard categories heading was modified.  
Section 4: First aid for skin contact - medical assistance - was modified.  
Section 4: First aid for inhalation - termination of exposure - was modified.  
Section 4: First aid for inhalation - medical assistance - was modified.  
Section 10: Hazardous polymerization heading was modified.  
Section 14: ID Number(s) and/or UPC(s) was modified.  
Section 2: Ingredient table was modified.  
Section 3: Other health effects information was modified.  
Section 16: HMIS explanation was modified.  
Section 16: NFPA explanation was modified.  
Section 15: 311/312 Delayed Hazard score was modified.  
Section 15: Inventories information was modified.  
Section 15: EPCRA 313 information was modified.  
Section 15: EPCRA 313 text was modified.  
Section 12: Ecotoxicological information heading was modified.  
Section 12: Chemical fate information heading was modified.  
Section 9: Density information was modified.  
Section 9: Vapor density value was modified.  
Section 5: Autoignition temperature information was modified.  
Section 5: Flash point information was modified.  
Section 9: Property description for optional properties was modified.  
Section 16: NFPA hazard classification for special hazards was modified.  
Section 9: Flash point information was modified.  
Section 9: Autoignition temperature information was modified.  
Section 12: Ecotoxicological phrase was modified.  
Section 12: Chemical Fate phrase was modified.  
Section 8: Eye/face protection comment was added.  
Section 8: Skin protection comment was added.  
Section 8: Respiratory protection comment was added.  
Section 3: Immediate skin hazard(s) was added.  
Section 4: First aid for skin contact - termination of exposure - was added.  
Section 4: First aid for skin contact - handling - was added.  
Section 2: Ingredient phrase was added.  
Section 8: Eye/face protection information was deleted.  
Section 8: Skin protection - recommended gloves information was deleted.  
Section 8: Respiratory protection - recommended respirators information was deleted.  
Section 8: Eye/face protection text was deleted.  
Section 8: Skin protection - recommended gloves text was deleted.  
Section 8: Respiratory protection - recommended respirators was deleted.  
Section 15: TSCA section 12[b] text was deleted.  
Section 9: Melting point information was deleted.  
Section 8: Respiratory protection - recommended respirators guide was deleted.  
Section 8: Skin protection - protective clothing text was deleted.  
Section 8: Respiratory protection - recommended respirators punctuation was deleted.  
Section 8: Eye/face protection information - punctuation - was deleted.  
Section 8: Skin protection - recommended gloves - punctuation was deleted.  
Section 15: TSCA section 12[b] information was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a

particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**