



Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SCOTCHGARD(TM) TILE AND GROUT PROTECTOR

MANUFACTURER: 3M

DIVISION: Commercial Care Division

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 01/10/2005

Supersedes Date: 12/31/2003

Document Group: 17-8304-2

Product Use:

Specific Use: Protects tile and grout from soiling

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	60 - 100
METHYL HYDROGEN POLYSILOXANE	63148-57-2	1 - 5
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2	< 0.9
N-OCTYLTRIETHOXSILANE	2943-75-1	< 0.5
TRIMETHYLATED SILICA	68988-56-7	< 0.5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Liquid

Odor, Color, Grade: White, slight odor.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards:

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

No health effects are expected.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. Get immediate medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

$\geq 212^{\circ}\text{F}$ [Test Method: Closed Cup]

Flammable Limits - LEL

No Data Available

Flammable Limits - UEL

No Data Available

OSHA Flammability Classification:

Class IIIB Combustible Liquid

5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: See Hazardous Decomposition section for products of combustion.

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition

information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Ventilate the area with fresh air. Contain spill. Cover or dilute with water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with water. Place in a closed container approved for transportation by appropriate authorities. Cover, but do not seal for 48 hours.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid breathing of vapors, mists or spray. Avoid prolonged or repeated skin contact. Avoid eye contact with vapors, mists, or spray. Avoid contact with oxidizing agents. Keep container closed when not in use. Keep out of the reach of children. Do not mix this product with alcohols or bases.

7.2 STORAGE

Store away from acids. Keep container in well-ventilated area. Store away from flammable and combustible materials. Store away from oxidizing agents. Protect from freezing.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust ventilation on open containers.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. Avoid eye contact with vapors, mists, or spray.
The following eye protection(s) are recommended: Indirect Vented Goggles.

8.2.2 Skin Protection

Gloves not normally required. Avoid prolonged or repeated skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber, Neoprene.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. Avoid breathing of vapors, mists or spray.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Inгредиент</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
OCTAMETHYLCYCLOTETRAILOXANE	CMRG	TWA	10 ppm	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists
CMRG: Chemical Manufacturer Recommended Guideline
OSHA: Occupational Safety and Health Administration
AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid
Odor, Color, Grade:	White, slight odor.
General Physical Form:	Liquid
Autoignition temperature	No Data Available
Flash Point	>=212 °F [Test Method: Closed Cup]
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available
Boiling point	>=150 °F
Density	1.001
Vapor Density	No Data Available
Vapor Pressure	<=27 mmHg
Specific Gravity	Approximately 1.001 [Ref Std: WATER=1]
pH	Approximately 3 Units not avail. or not appl.
Melting point	No Data Available
Solubility in Water	Complete
Evaporation rate	No Data Available
Volatile Organic Compounds	Approximately 1.5 % weight [Test Method: calculated per CARB title 2]
Percent volatile	<=99 %
VOC Less H2O & Exempt Solvents	<=550 g/l [Test Method: calculated per CARB title 2]
Viscosity	>=50 centipoise [Test Method: Brookfield]

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong acids; Strong bases; Strong oxidizing agents; Alcohols
Additional Information: This product will produce hydrogen gas if mixed with alcohols or bases.

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

Formaldehyde
Chlorine
Carbon monoxide
Carbon dioxide
Hydrogen Gas

During Combustion
During Combustion
During Combustion
During Combustion
Moisture

Hazardous Decomposition: Hazardous decomposition products may also include metal oxides and silicon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number
70-0709-9394-7
70-0709-9738-5

UPC
00-48011-29696-8
00-48011-29985-3

ID Number
70-0709-9408-5
70-0709-9739-3

UPC
00-48011-29697-5
00-48011-29986-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS**311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

STATE REGULATIONS**CHEMICAL INVENTORIES**

The components of this product are in compliance with the chemical notification requirements of TSCA.

The components of this product are listed on the Canadian Domestic Substances List.

INTERNATIONAL REGULATIONS**This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.****SECTION 16: OTHER INFORMATION****NFPA Hazard Classification****Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification**Health: 1 Flammability: 1 Reactivity: 0 Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

Reason for Reissue: European Statements**Revision Changes:**

Section 16: NFPA hazard classification heading was modified.

Section 16: HMIS hazard classification heading was modified.

Copyright was modified.

Section 8: Exposure guidelines data source legend was modified.

Section 3: Potential effects from eye contact was modified.

Section 3: Potential effects from skin contact information was modified.

Section 3: Potential effects from inhalation information was modified.

Section 7: Handling information was modified.

Section 7: Storage information was modified.

Section 8: Skin protection phrase was modified.

Section 15: 311/312 hazard categories heading was modified.

Section 10: Hazardous polymerization heading was modified.

Section 15: TSCA section 12[b] text was modified.

Section 16: HMIS explanation was modified.

Section 16: NFPA explanation was modified.

Section 15: Inventories information was modified.

Section 12: Ecotoxicological information heading was modified.

Section 12: Chemical fate information heading was modified.

Section 16: NFPA hazard classification for special hazards was modified.

Section 10: Hazardous decomposition heading was modified.

Section 16: Reason for reissue heading was modified.

Section 12: Ecotoxicological phrase was modified.

Section 12: Chemical Fate phrase was modified.

Section 2: Ingredient phrase was added.

Section 4: First aid for inhalation - none - was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com