

MATERIAL SAFETY DATA SHEET

7 INK & MARKER Carpet Spotter

Date Prepared: 08/17/2000 Date Revised: 08/17/2000

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name/Use: 7 INK & MARKER Carpet Spotter

MANUFACTURER

The Butcher Company 67 Forest Street Marlborough, MA 01752-3012

 Butcher Telephone Number:
 800-225-9475

 Emergency Telephone (24 hours):
 800-228-5635

 CHEMTREC (U.S./Can.):
 800-424-9300

 CHEMTREC (Int'l):
 +1 703-527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

| INGREDIENT(S) | CAS NO. | % BY WEIGHT | |
|-----------------------------------|----------|-------------|--|
| Triethanolamine | 102-71-6 | 10 - 25 | |
| Diethylene glycol monobutyl ether | 112-34-5 | 7 - 10 | |
| n-Butyl alcohol | 71-36-3 | 5 - 7 | |
| Hexylene glycol | 107-41-5 | 5 - 7 | |
| n-Amyl acetate | 628-63-7 | 1 - 1.5 | |
| Diethanolamine | 111-42-2 | 1 – 3 | |
| | | | |

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations. WHMIS CLASS: Class B- Division 3; Class D- Division 2B

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear, Light Yellow Liquid. Banana Odor. Combustible. May Cause Eye and Skin Irritation. May Be Harmful if Swallowed.

| POTENTIAL HEALTH EFFECTS (See See | ction 11 for Toxic | cological Information | n) |
|-----------------------------------|--------------------|-----------------------|-----------------|
| PRIMARY ROUTE(s) OF EXPOSURE: | <u>X</u> Eye | X Skin Contact | Skin Absorption |
| | X Inhalation | X Ingestion | |

EFFECTS OF ACUTE EXPOSURE

EYES:

May cause eye irritation. Symptoms may include redness and pain.

SKIN:

May cause skin irritation. Symptoms may include redness, rash and mild swelling.

MSDS No: 4348 Page: 1 of 7

INHALATION:

High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing and a burning sensation in the nose and throat. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

INGESTION:

May be harmful if swallowed. May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

EFFECTS OF CHRONIC EXPOSURE:

Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

MEDICAL CONDITIONS AGGRAVATED:

May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES:

Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN:

Flush thoroughly with plenty of water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops or persists. Thoroughly wash (or discard) clothing and shoes before reuse.

INHALATION:

Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION:

Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 119°F 48°C TCC

FLAMMABLE LIMITS

UPPER EXPLOSIVE LIMIT: 11.2% (n-butyl alcohol) LOWER EXPLOSIVE LIMIT: 1.4% (n-butyl alcohol)

AUTOIGNITION TEMPERATURE: Not applicable.

MSDS No: 4348 Page: 2 of 7

7 INK & MARKER Carpet Spotter

Date Prepared: 08/17/2000 Date Revised: 08/17/2000

EXTINGUISHING MEDIA:

Use water fog, dry chemical, CO2, or foam.

HAZARDOUS COMBUSTION PRODUCTS:

Normal products of combustion (carbon monoxide and carbon dioxide) and nitrogen oxides.

FIRE AND EXPLOSION HAZARDS:

Class II combustible liquid. This product is combustible and may be ignited by heat, sparks, flame, and other ignition sources. Vapors can travel to a source of ignition and flash back.

FIRE FIGHTING INSTRUCTIONS:

Evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Remove ignition sources and ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent and non-sparking tools to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING:

Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse.

STORAGE:

Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Store away from direct sunlight. Keep away from heat, sparks and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE:

Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN:

Where skin contact is possible, chemical-resistant clothing (e.g., gloves) should be worn.

RESPIRATORY:

No respiratory protection is required if general room ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits are exceeded, use appropriate respiratory protection (NIOSH/MSHA) to prevent overexposure.

MSDS No: 4348 Page: 3 of 7

ENGINEERING CONTROLS:

Good general room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

EXPOSURE LIMITS:

INGREDIENT(S) OSHA PEL/STEL ACGIH TLV/STEL

Triethanolamine NA 5 mg/m3
Diethylene glycol monobutyl ether NA NA

n-Butyl alcohol 100 ppm / /50 ppm (Ceiling, Skin)

50 ppm (Ceiling, Skin)

Hexylene glycol NA /25 ppm (Ceiling) NA /25 ppm (Ceiling) n-Amyl acetate 100 ppm (525 mg/m3) 100 ppm (532 mg/m3) Diethanolamine 3 ppm (15 mg/m3) 0.46 ppm (2 mg/m3)Skin

NA - Not Available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Banana

APPEARANCE: Clear, Light Yellow

pH: 8.3 to 9.3

PERCENT VOLATILE BY WEIGHT: 95 VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available BOILING POINT: Not Available

FREEZING/MELTING POINT: Not Available

SOLUBILITY IN WATER: Complete EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 0.99 VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID):

Stable.

POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION:

None.

MSDS No: 4348 Page: 4 of 7

INCOMPATIBLE MATERIALS:

Oxidizers (e.g., bleach) and strong acids (e.g., hydrochloric acid).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA:

No data is available for this product. The following data are available for product ingredients:

| PRODUCT/INGREDIENT | ORAL LD ₅₀ (rat) | DERMAL LD ₅₀ (rabbit) | INHALATION LC ₅₀ (rat) |
|-----------------------------------|-----------------------------|----------------------------------|-----------------------------------|
| Triethanolamine | 4000-9110 mg/kg | 2000 mg/kg | Not Available |
| Diethylene glycol monobutyl ether | 5660 mg/kg | 4120 mg/kg | Not Available |
| n-Butyl alcohol | 790–4400 mg/kg | 4200-5300 mg/kg | 8000 ppm (4-hr) |
| Hexylene glycol | 3700-4700 mg/kg | 7900-12000 mg/kg | Not Available |
| n-Amyl acetate | 6500-16600 mg/kg | >17500 mg/kg | Not Available |
| Diethanolamine | 710–3540 mg/kg | 12200 mg/kg | Not Available |

SENSITIZATION DATA:

No data available.

CHRONIC DATA:

Prolonged overexposure to n-butyl alcohol by ingestion and inhalation has caused central nervous system effects in humans and laboratory animals. Prolonged overexposure to high concentrations of triethanolamine by ingestion and dermal absorption has caused minor liver and kidney effects in laboratory animals.

REPRODUCTIVE/TERATOGENIC DATA:

No data available.

CARCINOGENIC/MUTAGENIC DATA:

Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA. In long-term animal studies with diethanolamine, increases in tumor formation were seen in mice, but not rats.

SYNERGISTIC MATERIALS:

No data available.

12. ECOLOGICAL INFORMATION

This product is made with all biodegradable detergents. No other data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA hazardous waste (Ignitable-D001) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

MSDS No: 4348 Page: 5 of 7

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated when in a container of 119 gallons (454 liters) or less.

15. REGULATORY INFORMATION

Not meant to be all-inclusive—selected regulations represented.

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed, Fire.

313 REPORTABLE INGREDIENTS: n-Butyl alcohol is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)
CERCLA REGULATORY: Not reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

| INGREDIENT(S) | CAS NO. | STATE LISTING |
|-----------------------------------|-----------|---------------|
| Water | 7732-18-5 | Not Listed |
| Triethanolamine | 102-71-6 | MA, PA |
| Diethylene glycol monobutyl ether | 112-34-5 | Not Listed |
| n-Butyl alcohol | 71-36-3 | Not Listed |
| Hexylene glycol | 107-41-5 | Not Listed |
| n-Amyl acetate | 628-63-7 | MA, NJ, PA |
| Diethanolamine | 111-42-2 | Ma, NJ, Pa |

NA - Not Applicable

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):

Class B-Division 3, combustible liquid; Class D-Division 2B, eye and skin irritant. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

MSDS No: 4348 Page: 6 of 7

16. OTHER INFORMATION

HMIS RATING

| HEALTH | - | 2 |
|---------------------|---|---|
| FLAMMABILITY | | 2 |
| REACTIVITY | | 0 |
| PERSONAL PROTECTION | 1 | - |

NFPA RATING FIRE 2 HEALTH 2 0 REACTIVITY SPECIAL

MSDS STATUS New MSDS

APPROVED BY: EH&S/Regulatory Affairs

APPROVAL DATE: 08/17/2000

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

MSDS No: 4348 Page: 7 of 7